



SOUND SOLUTIONS FROM LIGHT TECHNOLOGY



OPTIMIC™ 1140

Fiber Optic Microphone for Indoor Monitoring Applications

Miniature fiber optic microphone for indoor applications where the footprint for microphone is severely limited or where the microphone is a component in another device or system.

FEATURES

- ▶ Small, lightweight MEMS design
- ▶ Absolute EMI/RFI immunity
- ▶ Completely passive sensor with no metal or electrical parts
- ▶ Excellent sound accuracy
- ▶ Standard analog output
- ▶ High reliability and environmental stability
- ▶ Optical fiber connection over extended lengths without signal loss
- ▶ Exceptionally low sensitivity to vibration
- ▶ Plug-and-play system
- ▶ Cost-effective, long-term solution

TECHNICAL SPECIFICATIONS

Polar Pattern	Omnidirectional
Frequency Response	30-8,000 Hz
Conformity 30 - 1,000 Hz	±0.5 dB
Conformity 1,000 - 8000 Hz	±1.0 dB
Sensitivity	100 mV/Pa ±10% at 1 kHz
Equivalent Self-Noise	<31 dBA
Maximum Acoustic Pressure	144 dB SPL
Total Harmonic Distortion	<1% at 84 dB SPL
Equivalent Vibration Sensitivity	Max. 145 dB SPL/g at 1 kHz
Supply Voltage	8-15 V DC
Current Drain	80 mA ±10%
Operating Temperature	-20 to +60 °C (-4 to +140 °F)
Storage Temperature	-20 to +60 °C (-4 to +140 °F)
Humidity - 1000 hours	Up to 95% RH at 40 °C
MTBF	>100,000 hours
Microphone Head	
Material	Polycarbonate
Dimensions D/L	6/16 mm
Weight	0.5 g
Optical Cable Length	10 m

APPLICATIONS

- ▶ MRI/MEG scanners
- ▶ Highly explosive areas
- ▶ Aerospace measurements
- ▶ High voltage electrical utilities
- ▶ Petrochemical facilities
- ▶ Oil and gas detection sites
- ▶ Severe electromagnetic fields test labs



OPTIMIC™ 1140 System Kit


Complete, versatile cost-effective solution



Optoacoustics' OPTIMIC 1140 system is comprised of our advanced OPTIMIC fiber optic microphone, electro-optic unit, audio cable unit with BNC connector, DC power supply, and a ruggedized carrying case.

PRODUCT ORDERING GUIDE

Use the matrix below to select options and accessories for your order.



Options	Fiber Optic Cable Type		Electro-Optic Unit Type	
Item	Clear PVC Ø 1 mm	Kevlar reinforced black PVC Ø 3 mm	EOU 100 Single Channel	EOU 200 Single Channel
Code	P	F	A	B

Accessories	Extension Cable Type (Specify length from 10-100 m)			
Item	Outdoor, Milspec Ø 5 mm	Outdoor, Polyamide Ø 5.1 mm	Indoor, Rugged Ø 3.0 mm	Indoor, Zip Cord Ø 3.0 x 2 mm
Code	1	2	3	4



SOUND SOLUTIONS FROM LIGHT TECHNOLOGY

Optoacoustics is a leading manufacturer of high performance, optical fiber-based sound and vibration sensors. We combine the natural intelligence of optics and acoustics to meet technical performance demands which cannot be met by traditional microphones. Optoacoustics' pioneering technology is protected by over 20 international patents.

HEADQUARTERS TOLL-FREE 1 866-867-5029
17 Hanotea Street PHONE +972 3-634-4488
7316000 Mazor FAX +972 3-634-9292
Israel EMAIL info@optoacoustics.com

Copyright © 2019 Optoacoustics Ltd. All rights reserved. The information appearing without notice. Unless otherwise indicated, all product names are trademarks.